

Vibra-TITE®

Vibra-TITE offers a full line of adhesive products including threadlockers, thread sealants, retaining compounds, liquid gasketing, cyanoacrylates, anti-seize compounds, UV curables, epoxies, and more!



Vibra-TITE® Thread sealants

- Seals and secures metal pipes and fittings
- Fills the space between threaded metal parts
- Prevents leakage caused by tape shredding, vibration loosening, solvent evaporation, or damaged threads.
- Prevents corrosion and galling of threads.
- Low and high pressure applications.
- Seals to burst strength of most piping systems.
- Lubricating properties make assembly easier.
- Service removable; parts may be disassembled with basic hand tools.

Vibra-TITE®



ITEM NO.	COMPARES TO LOCTITE PART#	MAX GAP FILL	SEALING PRESSURE (PSI)	TEMP RANGE	FIXTURE TIME (MIN.)	SIZE	PRICE EACH				
							1	6	12	24	48
Vibra-Tite 420 PTFE Instant Pipe Sealant - Industrial Grade with controlled lubricity, prevents galling while protecting from corrosion and rust. Parts may be repositioned up to 24 hours after assembly. Typical uses include stainless steel and all other metal fittings. White. COMPRES WITH LOCTITE® 565/592.											
915390	56531/ 59231	0.012	10,000	-65°F to 300°F	60	50 mL Bottle	\$14.46	\$13.62	\$12.88	\$12.21	\$11.60
915393	56541/ 59241					250 mL Tube	48.51	45.70	43.19	40.95	
							1	3			
915395						1 L Jug	\$148.71	\$140.21			
Vibra-Tite 440 Hydraulic and Pneumatic High Pressure Sealant with excellent solvent resistance. It locks hydraulic and pneumatic connections producing a high strength, high pressure seal, while allowing easy disassembly with standard tools. For pneumatic, small pipe threads, and hydraulic fittings up to 2" diameter. Purple. COMPARES WITH LOCTITE® 545											
		0.007	10,000	-65°F to 300°F	30		1	6	12	24	48
915410	32429					10 mL Bottle	\$8.72	\$8.22	\$7.77	\$7.36	\$7.00
915413	54531					50 mL Bottle	22.03	20.75	19.62	18.60	17.68
915416	54541					250 mL Tube	71.82	67.65	63.95	60.62	
							1	3			
915419						1 L Jug	\$170.11	\$160.39			
Vibra-Tite 442 Hydraulic Fast Cure Sealant is a fast curing gel thread sealant which withstands temperatures up to 300°F. Purple. COMPARES WITH LOCTITE® 5452.											
		10,000	-65°F to 300°F				1	6	12	24	48
915450	1265769					50 mL Tube	\$21.54	\$20.29	\$19.18	\$18.18	\$17.28
915453	1265770					250 mL Tube	73.45	69.19	65.40	62.00	
Vibra-Tite 444 Hydraulic High Pressure Sealant is a general purpose pipe sealant that creates an instant seal on threaded joints with a high resistance to solvents and withstands temperatures to 300°F. Typical uses: small pipe threads and hydraulic fittings. Brown. COMPARES WITH LOCTITE® 569.											
915470		0.007	10,000	-65°F to 300°F	10	10 mL Bottle	\$8.72	\$8.22	\$7.77	\$7.36	\$7.00
915473	56931					50 mL Bottle	20.15	18.99	17.95	17.01	16.17
915476	56941					250 mL Tube	71.82	67.65	63.95	63.95	
							1	3			
915479						1 L Jug	\$170.11	\$160.39			
Vibra-Tite 460 High Temperature - Stainless Steel Pipe Sealant prevents galling and provides an instant low pressure seal on coarse fitting threads which is further strengthened as the product cures. Assembled parts can withstand temperatures up to 400°F and may be repositioned up to 24 hours after assembly. Typical uses include stainless steel, aluminum , galvanized metal and other inert metal threaded pipe fittings. White. COMPARES WITH LOCTITE® 567.											
		0.012	10,000	-65°F to 400°F	60		1	6	12	24	48
915490	56707					6 mL Tube	\$4.45	-	\$4.19	\$3.96	\$3.75
915493	56747					50 mL Bottle	14.46	13.62	12.88	12.21	11.60
915496	56765					250 mL Tube	48.51	45.70	43.19	40.95	
							1	3			
915498						1 L Jug	\$148.71	\$140.21			
Vibra-Tite 480 Multi-Purpose FBC Compatible Thread Sealant with PTFE is designed to lubricate and seal threaded connections. A non-curing and non-toxic formula, Vibra-Tite 480 contains no lead or harmful metals and can be used in potable water systems. White.											
		10,000	-35°F to 500°F				1	6	12	24	48
915510						4 oz. Jar with Brush	\$20.92	\$19.71	\$18.63	\$17.66	\$16.79
915513						8 oz. Jar with Brush	30.62	28.84	27.26	25.84	24.57
Vibra-Tite 612 Excel Primer T with PTFE is the recommended primer that can be used for the above thread sealants (except Vibra-Tite 480). COMPARES WITH LOCTITE® 7471.											
915680	Fast acting primer, acetone / isopropanol. Up to 7 days on-part life, dry time is 30 to 70 seconds.					2 oz. bottle	\$7.38	\$6.97	\$6.61	\$6.28	\$5.98
915683						8 oz. bottle	17.35	16.35	15.45	14.65	13.93

Phone: (855) 4ZDRILL

Order Email: orderdesk@zdrill.net

Fax: (855) 390-3430

- For locking and sealing threaded fasteners.
- Liquid threadlockers are considered to be the most effective method of locking threaded fasteners because they unitize the entire assembly.
- They perform better than traditional mechanical devices such as lock washers.
- Prevents any loosening from shock or vibration, as well as alleviating rust-lock and preventing leakage.
- Vibra-Tite 121, 122, 131, & 140 are available in a handy counter-top fishbowl display stocked with 100 of the 2mL tubes. Attractive way to boost sales at the counter. Each 2mL resealable bullet tube will do 15 to 25 applications.



ITEM NO.	COMPARES TO LOCTITE PART#	MAX GAP FILL	TORQUE STRENGTH, BREAK/ PREVAIL(LB)	TEMP RANGE	FIXTURE TIME (MIN.)	SIZE	PRICE EACH				
							1	6	12	24	48
Vibra-Tite 121 Medium, Removable Strength Threadlocker that seals nuts and bolts allowing disassembly using standard tools. Typical uses include locking nuts or bolts from 1/4" to 3/4" in diameter. Blue. COMPARES WITH LOCTITE® 242.											
915100	24221	0.007	120 / 45	-65°F to 300°F	10 - 30	10 mL Bottle	\$7.69	\$7.25	\$6.85	\$6.49	\$6.17
915103	24231					50 mL Bottle	21.78	20.52	19.40	18.39	17.48
915109	24241					250 mL Bottle	71.31	67.17	63.49	60.19	
							1	2	3	4	
915110						1L Jug	\$152.94	-	\$144.20	-	
915112						100 1.8 mL tubes	107.69	101.45	-	95.89	
Vibra-Tite 122 Medium Strength Threadlocker with greater oil tolerance. Typical uses include locking nuts or bolts ranging from 1/4" to 3/4" in diameter. Blue. COMPARES WITH LOCTITE® 243.											
		0.015	195 / 70	-65°F to 300°F	5 - 10		1	6	12	24	48
915130	24077					10 mL Bottle	\$7.77	\$7.32	\$6.92	\$6.56	\$6.23
915133	24078					50 mL Bottle	22.51	21.20	20.04	19.00	18.06
915139	24079					250 mL Bottle	74.48	70.16	66.32	62.87	
							1	2	3	4	
915142	21433					1L Jug	\$156.06	-	\$147.14	-	
915145						100 1.8 mL tubes	107.69	101.45		95.89	
Vibra-Tite 125 Medium Strength Threadlocker, Gel. Removable grade for fasteners 1/4" to 3/4". Blue.											
		0.015	120 / 45	-65°F to 300°F	10 - 30		1	6	12	24	48
915170						6 mL Tube	\$4.74	-	\$4.46	\$4.22	\$4.00
915173						35 mL Pump	17.43	16.42	15.52	14.71	13.99
915176						50 mL Tube	22.98	21.65	20.47	19.40	18.44
915179						250 mL Tube	60.55	57.04	53.92	53.92	48.59
Vibra-Tite 131 High Strength Permanent Threadlocker for maximum security suitable for most applications where disassembly is not required. Designed to withstand extreme environmental conditions and chemical exposure. Ideal for the prevention of rust and corrosion. Typical uses include permanently locking nuts or bolts up to 1" in diameter. Heat and hand tools are needed for disassembly. Red. COMPARES WITH LOCTITE® 262.											
915200	26221	0.007	200 / 250	-65°F to 300°F	5 - 20	10 mL Bottle	\$7.69	\$7.25	\$6.85	\$6.49	\$6.17
915203	26231					50 mL Bottle	21.78	20.52	19.40	18.39	17.48
915209	26241					250 mL Bottle	71.31	67.17	63.49	60.19	
							1	2	3	4	
915212	26243					1L Jug	\$152.94	-	\$144.20	-	
915215						100 1.8 mL tubes	107.69	101.45	-	95.89	
Vibra-Tite 132 High Strength Primerless Threadlocker, Oil Tolerant, Red											
		0.007	275 / 290	360°F	5		1	6	12	24	48
915230	1330583					10 mL Bottle	\$8.57	\$8.07	\$7.63	\$7.23	\$6.88
915233	1330585					50 mL Bottle	22.18	20.90	20.90	18.73	17.80
915236	1330335					250 mL Bottle	83.65	78.80	74.48	70.61	
							1	3			
915239						1L Jug	\$166.77	\$157.24			



Vibra-TITE® Threadlockers - (continued)

ITEM NO.	COMPARES TO LOCTITE PART#	MAX GAP FILL	TORQUE STRENGTH, BREAK/PRE-VAIL(LB)	TEMP RANGE	FIXTURE TIME (MIN.)	SIZE	PRICE EACH				
							1	6	12	24	48
Vibra-Tite 135 High Strength Permanent Threadlocker, Gel Red											
915250		0.015	200 / 100	-65°F to 300°F	5 - 20	6 mL Tube	\$4.74	-	\$4.46	\$4.22	\$4.00
915253						35 mL Pump	17.43	16.42	15.52	14.71	13.99
915256						50 mL Bottle	22.98	21.65	20.47	19.40	18.44
							1	6	12	24	
915259						1 L Jug	\$60.55	\$57.04	\$53.92	\$51.12	
Vibra-Tite 140 High Strength Threadlocker for maximum security. Suitable for most applications where disassembly is not required. Typical uses include permanently locking nuts or bolts up to 1" in diameter. Heat and hand tools are needed for disassembly. Red. COMPARES WITH LOCTITE® 271.											
		0.007	250 / 275	-65°F to 300°F	10 - 30		1	6	12	24	48
915280 27121						10 mL Bottle	\$7.69	\$7.25	\$6.85	\$6.49	\$6.17
915283 27131						50 mL Bottle	21.78	20.52	19.40	18.39	17.48
915286 27141						250 mL Bottle	71.31	67.17	63.49	60.19	
							1	2	3	4	
915287						1 L Jug	\$152.94	-	\$144.20		
915289						100 1.8 mL tubes	107.69	101.45		95.89	
Vibra-Tite 146 Large Diameter High Strength Threadlocker for permanently locking up to 1-1/2" diameters. Red. COMPARES WITH LOCTITE® 277.											
		0.010	300 / 250	-65°F to 300°F	10 - 20		1	6	12	24	48
915310 21434						10 mL Bottle	\$7.69	\$7.25	\$6.85	\$6.49	\$6.17
915313 27731						50 mL Bottle	21.78	20.52	19.40	18.39	17.48
915316 27741						250 mL Bottle	71.31	67.17	63.49	60.19	
							1	3			
915319		1 L Jug	\$152.94	\$144.20							
Vibra-Tite 150 Wicking Grade, Medium Strength Threadlocker designed specifically for use on pre-assembled connections. Seals small gaps through capillary action. For pre-assembled fasteners up to 1/2" in diameter and porous die castings. Protects welds from rust and corrosion. Hand tools are needed for disassembly. Green. COMPARES WITH LOCTITE® 290.											
		0.004	85 / 250	-65°F to 300°F	5 - 20		1	6	12	24	48
915330 29021						10 mL Bottle	\$7.69	\$7.25	\$6.85	\$6.49	\$6.17
915333 29031						50 mL Bottle	21.78	20.52	19.40	18.39	17.48
915336 29041						250 mL Bottle	71.31	67.17	63.49	60.19	
							1	3			
915339 29043		1L Jug	\$152.94	\$144.20							
Vibra-Tite VC-3 Threadmate is a unique, locking and sealing coating for threaded fasteners that works on the principle of “friction through viscosity”. Stops fasteners from loosening from extreme shock and vibration. Works with metal, wood, PP and PPE plastics and more. Fasteners are easily adjusted, removed, and reused. Works with internal and external threads, on fasteners of any shape or size from tiny eyeglass screws to large construction bolts. Red.											
							1	6	12	24	48
915360						5 mL Tube	\$5.23	\$4.93	\$4.66	\$4.42	\$4.20
							1	6	10	20	30
915363						30 mL Tube	26.46	-	24.93	23.56	22.34
915366						250 mL Tube	107.83	101.58			
							1	2	4		
915369						1 Quart	\$303.76	\$286.89			
915372						1 Gallon	808.43	769.93			
915359						100 1.8 mL tubes	84.62	79.71	75.34		

Vibra-TITE® Retaining Compounds

- Designed to increase shear strength in non-threaded, cylindrical metal assemblies.
- The liquid anaerobic material fills voids between close-fitting metal assemblies.
- It cures to a toughened thermoset-plastic which creates a solid one piece assembly.
- Retaining compounds seal joints against leakage and prevent corrosion.
- These materials have gained wide acceptance as a standard method for assembling press-fit and slip-fitted parts.
- Vibra-Tite 541 is available in a handy counter-top fishbowl display stocked with 100 of the 2mL tubes. Attractive way to boost sales at the counter. Each 2mL resealable bullet tube will do 15 to 25 applications.



ITEM NO.	COMPARES TO LOCTITE PART#	MAX GAP FILL	SHEAR STRENGTH (PSI)	TEMP RANGE	FIXTURE TIME (MIN.)	SIZE	PRICE EACH				
							1	6	12	24	48
Vibra-Tite 530 General Purpose Retaining Compound bonds metal assemblies. A low viscosity retaining compound recommended for diametral gap distances up to 0.005" to augment press fits. Withstands temperatures of up to 300°F providing a shear strength of 3000 PSI after 24 hours with fixture time of 10 minutes. Typical uses: Rotors, shafts, bushings, bearings, and pulleys. COMPARES WITH LOCTITE® 609/675.											
915530	60921	0.005	2300+	-65°F to 300°F	10 - 20	10 mL Bottle	\$7.68	\$7.23	\$6.84	\$6.48	\$6.16
915533	60931					50 mL Bottle	22.03	20.75	19.62	18.60	17.68
915536	60941 / 67541					250 mL Bottle	73.86	69.58	65.77	62.35	
							1	3			
915537						1L Jug	\$151.67	\$143.00			
Vibra-Tite 541 High Strength Retaining Compound cures in room temperatures filling diametral gaps up to 0.015". Typical uses include fitted cylindrical parts replacing set screws, clamp rings, and snap rings. It provides a shear strength greater than 3000 PSI after 24 hours with a fixture time of 10 minutes. COMPARES WITH LOCTITE® 680.											
		0.015	3000+	-65°F to 300°F	20 - 40		1	6	12	24	48
915560	68015					10 mL Bottle	\$7.68	\$7.23	\$6.84	\$6.48	\$6.16
915563	68035					50 mL Bottle	6.16	20.75	19.62	18.60	17.68
915566	68060					250 mL Bottle	73.86	73.86	65.77	62.35	
							1	2	3	4	
915567						1L Jug	\$151.67	-	\$143.00	-	
915569						100 1.8 mL tubes	107.69	101.45	-	95.89	
Vibra-Tite 542 High Strength Retaining Compound is a high viscosity retaining compound that allows parts to be adjusted during assembly. It provides a shear strength greater than 4000 PSI. Typical uses include slip fit components, rotors, shafts, impellers, and splines. COMPARES WITH LOCTITE® 635.											
		0.015	4000+	-65°F to 300°F	20 - 40		1	6	12	24	48
915590						10 mL Bottle	\$7.68	\$7.23	\$6.84	\$6.48	\$6.16
915593	63531					50 mL Bottle	22.03	20.75	19.62	18.60	17.68
915596	63541					250 mL Bottle	73.86	69.58	65.77	62.35	
							1	3			
915597						1L Jug	\$151.67	\$143.00			
Vibra-Tite 548 Press Fit / Rapid Cure works with continuous operating temperatures up to 350°F. Provides a shear strength greater than 3500 PSI. COMPARES WITH LOCTITE® 648.											
		0.007	3500+	-65°F to 300°F	5		1	6	12	24	48
915620	21444					50 mL Bottle	\$22.03	\$20.75	\$19.62	\$18.60	\$17.68
915623	21445					250 mL Bottle	73.86	69.58	65.77	62.35	
							1	3			
915626						1L Jug	\$151.67	\$143.00			
Vibra-Tite 560 High Temp Fast Set Retaining Compound is a high temp, high strength adhesive for retention of cylindrical components, where disassembly is not required on press-fit assemblies. Typical uses include rotors, shafts, bushings, bearings, and pulleys with temps up to 400°F. It provides a shear strength greater than 3000 PSI. COMPARES WITH LOCTITE® 640.											
		0.007	3000+	-65°F to 400°F	5 – 60		1	6	12	24	48
915650						10 mL Bottle	\$7.68	\$7.23	\$6.84	\$6.48	\$6.16
915653	64031					50 mL Bottle	22.03	20.75	19.62	18.60	17.68
915656	64041					250 mL Bottle	73.86	69.58	65.77	62.35	
							1	3			
915657						1L Jug	\$151.67	\$143.00			

Vibra-TITE®

Vibra-TITE® Anti-Seize Compounds

- Specially formulated to prevent seizing, galling, pitting, excessive wear, and corrosion.
- Will not wash, squeeze, or burn out, even at elevated temperatures and pressure.
- Reduces friction and wear, eases assembly and disassembly.
- Typical applications include gears, chains, cables, sprockets, and fastener threads.
- Convenient brush-cap applicator.



ITEM NO.	COMPARES TO LOCTITE PART#	VISCOSITY (cP)	SEALING PRESSURE (PSI)	TEMP RESISTANCE	K-VALUE	SIZE	PRICE EACH				
							1	6	12	24	
Vibra-Tite 9070 Aluminum Anti-Seize Compound This lubricant is ideal for all metals to prevent seizing, galling and excessive wear. Resists harsh chemical environments. Consists of fine flakes of aluminum and graphite suspended in a blend of lubricants and oils. Silver color. COMPARES WITH LOCTITE® Silver.											
915798		120,000 to 175,000 Paste		1800°F	0.15	35 mL Pump with Brush	\$7.92	\$7.46	\$7.05	\$6.69	
915800 76732						8 oz. Jar with Brush	15.08	14.20	13.42	12.73	
915803 76764						16 oz. Jar with Brush	23.66	22.29	21.07	19.97	
							1	2	4		
915806						1 Gallon Bottle	\$166.15	\$156.66			
915809						5 Gallon Pail	579.25	549.92			
915812						100 1.8 mL tubes	143.08	134.78	127.40		
Vibra-Tite 9071 Copper Anti-Seize Compound Ideal for use on softer metal parts such as copper and brass. Protects from rust and corrosion as well as prevents seizing, galling and excessive wear. Excellent resistance to harsh chemical environments. Consists of fine flakes of copper and graphite suspended in a blend of lubricants and oils. Copper color. COMPARES WITH LOCTITE® C5-A.											
		120,000 to 175,000 Paste		1800°F	0.15		1	6	12	24	
915820 51144						4 oz. Jar with Brush	\$8.46	\$7.97	\$7.53	\$7.14	
915823 51147						8 oz. Jar with Brush	13.03	12.28	11.60	11.00	
915826 51007						16 oz. Jar with Brush	17.97	16.93	16.00	15.17	
							1	2			
915829						1 Gallon Bottle	\$155.50	\$146.61			
915832						5 Gallon Pail	425.39	403.85			
Vibra-Tite 9072 Nickel Anti-Seize Compound A lubricant ideal for extreme temperatures. Copper and graphite free base. Resistant to harsh chemical environments. Excellent for stainless steel and other metal fittings. COMPARES WITH LOCTITE® Nickel.											
				2600°F			1	6	12	24 48	
915848						8 mL Tube	\$4.25	-	\$4.00	\$3.78	\$3.58
915850 77124						8 oz. Jar with Brush	18.22	17.16	16.22	15.38	
915853 77164						16 oz. Jar with Brush	28.77	27.10	25.62	24.29	
							1	2	3	4	
915856						1 Gallon Bottle	\$201.21	\$189.71			
915859						5 Gallon Pail	692.50	659.52			
915862						100 1.8 mL tubes	143.08	134.78	127.40		

Vibra-TITE®

Vibra-TITE® Anaerobic Gasketing

- Remains liquid when exposed to air; cures when confined between mating flanges.
- Can fill gaps as large as 0.050.
- Alleviates the need for preformed gaskets.
- Typical applications include form-in-place gaskets for thermostats, pumps, gearboxes, compressors, transmission housings, and axle covers.



ITEM NO.	COMPARES TO LOCTITE PART#	MAX GAP FILL	VISCOSITY (cP)	TEMP RANGE	CURE SPEED (HRS)	SIZE	PRICE EACH				
							1	6	12	24/30	48
Vibra-Tite 709 Flexible Gasket Maker Flexible flange sealant resists vibration. Fluorescent blue color aids visual assembly inspections. Blue. COMPARES WITH LOCTITE® 509.											
915700		Unprimed: 0.010	65,000 – 200,000	-65°F to 300°F	Unprimed: 6 - 48	50 mL Tube	\$20.74	\$19.54	\$18.47	\$17.51	\$16.64
915703	21525	Primed: .020	Thixotropic		1 - 6	300 mL Cartridge	76.92	72.46	68.49	64.94	
Vibra-Tite 710 High Temperature Rigid Flange Sealant withstands temperatures up to 400°F. Pink. COMPARES WITH LOCTITE® 510.											
915710	51031	Unprimed: 0.010	188,000	-65°F to 400°F	Unprimed: 4 - 24	50 mL Tube	\$20.74	\$19.54	\$18.47	\$17.51	\$16.64
915713	51041	Primed: 0.020	– 500,000		Primed: 0.5 - 4	250 mL Tube	50.89	47.94	45.32	42.96	
915716	51074		Thixotropic			300 mL Cartridge	67.86	63.93	60.42	57.29	
Vibra-Tite 730 Flexible Gasket Maker – Solvent Resistant is suitable for aluminum and rigid machined flanges. Red. COMPARES WITH LOCTITE® 518.											
915750	51831	Unprimed: 0.010	80,000 – 3,750,000	-65°F to 300°F	Unprimed: 1 - 12	50 mL Tube	\$20.74	\$19.54	\$18.47	\$17.51	\$16.64
915753		Primed: 0.020	Thixotropic		Primed: 0.25 - 2	250 mL Tube	50.89	47.94	45.32	42.96	
915756	51845					300 mL Cartridge	67.86	63.93	60.42	57.29	
Vibra-Tite 732 Flexible Gasket Maker General purpose gasket maker that flexes with flanges. Purple. COMPARES WITH LOCTITE® 515.											
915770	51531	Unprimed: 0.010	275,000	-65°F to 300°F	Unprimed: 4 - 24	50 mL Tube	\$20.74	\$19.54	\$18.47	\$17.51	\$16.64
915773		Primed: 0.020	– 950,000		Primed: 0.5 - 4	250 mL Tube	50.89	47.94	45.32	42.96	
915776	51580		Thixotropic			300 mL Cartridge	67.86	63.93	60.42	57.29	

Vibra-TITE®

KITS OFFER A SELECTION OF POPULAR PRODUCTS FOR TOOLBOX OR SHOP.

Vibra-TITE® FAST LOCK 4™ 4-Piece Threadlocking Kit

Includes:

- 12110 Medium Strength Removable
- 13110 Permanent Strength Threadlocker
- 12535 Medium Strength Gel Threadlocker
- 47002 Anti Cam-Out Fluid



ITEM NO.	DESCRIPTION	1 kit	4	8	12
915910	4-pc Fast Lock Pack	\$31.51	\$29.68	\$28.05	\$26.60

Vibra-TITE® WORK PACK 6-Piece Products Kit

Includes:

- 21305 VC-3 Threadmate nontraditional threadlocker
- 13508 Permanent strength (red) threadlocker gel
- 12508 Medium strength (blue) threadlocker gel
- 30114 Multi-purpose Instant SuperGlue
- 47002 DriveGrip Anti Cam-Out fluid
- 90729 Nickel-graphite anti-seize compound



ITEM NO.	DESCRIPTION	1 kit	4	8	12
915920	6-pc Work Pack	\$33.28	\$31.35	\$29.63	\$28.09

Vibra-TITE® BENCH PACK 5-Piece Locking & Retaining Kit

Includes:

- 54110 High Strength Retaining Compound
- 15010 Wicking Grade, Medium Strength Thread-locker
- 12110 Medium Strength Removable Threadlocker
- 14010 High Strength Threadlocker
- 47002 Anti Cam-Out Fluid



ITEM NO.	DESCRIPTION	1 kit	4	8	12
915900	5-pc Bench Pack	\$41.92	\$39.49	\$37.33	\$35.39



J-B Weld

- J-B WELD is an easy, convenient, and inexpensive alternative to welding. J-B Weld will bond to virtually any clean, dry surface including: iron, steel, copper, aluminum, brass, bronze, pewter, porcelain, ceramic, marble, glass, concrete, fiberglass, wood, some plastics and more.
- STEELSTIK formula is a hand knead-able, steel-reinforced epoxy putty adhesive/sealant that will plug holes and make repairs on wet and dry surfaces. Will cure even when completely submerged in water or gasoline.
- MARINE WELD formula is as strong as steel and water- and weather-proof.
- KWIK formula has a set time of only 4 minutes.
- WATER WELD formula is an epoxy putty that will plug holes and make permanent repairs in moist surface or underwater applications. Will even repair leaking fuel tanks. Approved for use with potable water.

ITEM NO.	DESCRIPTION	1	6	12	24
228700	ORIGINAL COLD WELD™ Formula	\$6.80	\$6.42	\$6.08	\$5.78
228703	STEELSTIK™ Universal Epoxy Putty	6.37	6.02	5.70	5.42
228706	MARINE WELD™ Welding Compound	5.88	5.56	5.26	5.00
228709	KWIK® Welding Compound	5.00	6.52	6.17	5.87
228712	WATER WELD Epoxy Stick	6.89	6.50	6.16	5.85
		1	3	6	9
228715	INDUSTRO WELD Cold Welding Compound, (2) 5 oz Tubes - Boxed, Price Per Box	12.09	11.42	10.82	10.28



Metabo® W9-115 Quick Angle Grinder

- Powerful 8.5 amp Long Life motor with patented dust guard, up to 20% more high overload capacity and 50% more torque.
- Ergonomically designed body and handle make for lower fatigue and increased productivity.
- The Metabo M-Quick System allows for quick disc change at the touch of a button, without tools.
- Features tool-free and twist-proof adjustable guard.
- Metabo S-automatic Torque Limiting Clutch minimizes kick-back to the lowest level when the disc jams unexpectedly – for maximum user protection and swift progress.
- Gear housing can be mounted turned in 90° steps for left-handed or cutting operations.
- No-load RPM: 10500, At rated load RPM: 7500, Torque: 22 in-lbs
- Spindle thread: 5/8"-11 UNC, Weight: 4.6 lbs [w/o cord], Cord length: 8'



ITEM NO.	DESCRIPTION	1	2	4	6
220410	4-1/2" Angle Grinder	\$208.93	\$197.63	\$187.50	\$178.35

Malco Hand Riveter

- Lightweight, compact size and slim nose projection allows this riveter to go wherever the work is.
- Four nosepieces: 3/32, 1/8, 5/32, and 3/16 in. store in handle.
- Rugged steel construction, spring return handles, and comfortable contour grips make operation fast and easy.
- Not for use with 5/32" or 3/16" steel rivets (steel rivets larger than 3.2 mm).



ITEM NO.	DESCRIPTION	1	3	6	12
220008	CR18 economy riveter	\$33.37	\$31.68	\$30.16	\$28.77

Malco 2IN1 Hand Riveter

- One hand operation made easy!
- Includes 3 nose pieces: 1/8, 5/32, & 3/16", store in handle.
- Professional slim nose allows 2-in-1 to go where other hand riveters cannot.
- Heavy-duty all steel construction insures long life.
- Red vinyl cushion grip and hand stop.



ITEM NO.	DESCRIPTION	1	2	4	8
220010	2-in-1 hand riveter	\$92.01	\$87.35	\$83.14	\$79.32

Slic-tite® PTFE Thread Tape

- Pressure: to 2,000 PSI
- Sealing temperature: -450°F to 550°F.
- 4 mils thick and made with PTFE for greater sealing power.
- Non-toxic
- Yellow is for gas line usage.
- Pink is for water line usage.

LA-CO®



ITEM NO.	DESCRIPTION	1	12	48	96
228400	White 1/2" x 300'		\$2.67	\$2.53	\$2.40
228407	White 1/2" x 600'	3.65	3.44	3.26	3.10
228414	Yellow 1/2" x 260'		2.42	2.29	2.18
228421	Pink 1/2" x 260'	2.42	2.42	2.29	2.18

Clamp Fixtures

- Mounts on any length of 3/4" black pipe with threaded ends.
- 223653 with 1-3/4 in. wide jaws has a crank handle.
- 223659 with 2-1/2 in. wide jaws has a wing-nut style handle.
- Both come with a coil spring "stop" to thread onto the opposite end of the pipe.

ANCHOR BRAND®



ITEM NO.	DESCRIPTION	1 set	5	10	20
223653	Jaw width: 1-3/4"	\$31.38	\$29.64	\$28.08	\$26.68
223659	Jaw width: 2-1/2"	37.26	35.19	33.34	31.67

Dual-Range Non-Contact Voltage Tester

KLEIN TOOLS

- Automatically detects and indicates low voltage (12-48 Volts AC) and standard voltage (48-1000 Volts AC), allowing broad application.
- Non-contact detection of standard voltage in cables, cords, circuit breakers, lighting fixtures, switches, outlets, and wires.
- Non-contact detection of low-voltage in security, entertainment, communications, environmental control, and irrigation systems.
- High intensity, bright green or blue LED indicates the tester is operational and aids in illuminating the workspace.
- Digitally controlled ON/OFF power button.
- Auto power-off feature conserves and extends battery life.
- Microprocessor controlled low battery indicator.
- CAT IV 1000 Volt rating provides expanded operation and protection.
- Lightweight, durable polycarbonate plastic resin construction with a convenient pocket-clip.
- Package contains insert card with integrated owner's manual and
- 2 AAA 1.5 volt batteries.
- Frequency range 50-500 Hz



ITEM NO.	DESCRIPTION	1	4	8	16
225500	Voltage tester	\$35.44	\$33.48	\$31.71	\$30.13

CG20 Professional Caulking Gun

- Square piston design.
- Minimizes worker fatigue.
- User can regulate stroke to fit hand.
- Handy puncture wire folds inside handle.
- Weight: 28 oz.
- 1/10 gallon cartridge capacity.



ITEM NO.	DESCRIPTION	1	5	10	20
223321	CG-20 caulking gun	\$40.21	\$38.18	\$36.34	\$34.67

CG18 Easy Dispensing Caulking Gun

- Rotating barrel for maneuverability and easy caulk placement.
- Double-gripping plate for greater durability.
- Trigger adjustment screw compensates for normal wear to assure full dispensing stroke and extend life.
- Weight: 28 oz.
- 1/10 gallon cartridge capacity.



ITEM NO.	DESCRIPTION	1	5	10	20
223314	CG-18 caulking gun	\$7.59	\$7.20	\$6.86	\$6.54

CG12 Flexible / Lightweight Caulking Gun

- Compact design stores in a toolbox.
- Handy puncture wire.
- Ladder size hang hook.
- Weight: 25 oz.
- 1/10 gallon cartridge capacity.



ITEM NO.	DESCRIPTION	1	5	10	20	50
223307	CG-12 caulking gun	\$7.59	\$7.20	\$6.86	\$6.54	\$6.25

CG10 Utility Caulking Gun

- Weight: 17 oz.
- 1/10 gallon cartridge capacity.



ITEM NO.	DESCRIPTION	1	5	10	20	50
223300	CG-10 caulking gun	\$6.06	\$5.72	\$5.42	\$5.15	\$4.90





Industrial Carton Sealing Tape

- 2.0 mil, 400 Series industrial carton sealing tape.
- Crystal clear tape will not yellow over time.
- Use for medium to heavy-weight carton sealing.
- Also available in a 6 roll case.



ITEM NO.	SIZE	THICKNESS	PRICE PER ROLL			
			1 roll	36	72	144
079330	2" x 110 yds	2 mil	\$2.33	\$2.22	\$2.11	\$2.01
079333	3" x 110 yds	2 mil	3.49	3.32	3.16	3.01

Filament Strapping Tape

- 1300 Series economy filament strapping tape.
- Tensile strength: 100 lb.



ITEM NO.	SIZE	WEIGHT	PRICE PER ROLL			
			1 roll	36	72	144
300000	1" x 60" yds	100 lbs.	3.61	3.43	3.27	3.11
300010	1" x 60" yds	130 lbs.	5.92	5.62	5.35	5.10
300020	1" x 60" yds	160 lbs.	6.17	5.86	5.58	5.32

Scotch® Super 33+™ Electrical Tape

- Withstands harsh conditions while protecting and insulating.
- Performs in 0° - 220° F.
- The combination of elastic backing and aggressive adhesive provides moisture-tight electrical and mechanical protection with minimum bulk.
- Pressure sensitive rubber based adhesive.
- Thickness: 7 mil.



ITEM NO.	DESCRIPTION	1	5	10	20	50
228020	3/4" x 66'	\$5.79	\$5.47	\$5.18	\$4.93	\$4.69

General Purpose Electrical Tape

- Vinyl electrical tape features excellent adhesion and elongation properties.
- General purpose for household and industrial.
- Thickness: 7 mil.



ITEM NO.	DESCRIPTION	1	10	50	100	200
228010	3/4" x 60'	\$1.12	\$1.06	\$1.00	\$0.95	\$0.91